

March 2021

Ref:	V 1.01
Product Family:	Conventional
Product Range:	H ₂ O - Conventional

H₂O Series Precision Moisture Sensor



BC5070
#PFC-0201SS

<p>Andrew Snell +44 (0) 7967 300578 Andrew@pfc-eu.com</p>	<p>PLEASE CONSULT YOUR PRICE GUIDE FOR ALL AVAILABLE OPTIONS FOR THIS MODEL</p>	<p>Conventional</p>	
---	---	---------------------	---

SALES & PRODUCT INFORMATION

H₂O - Moisture Sensor

The system utilises electrical conductivity between measuring starwheels either side of the bale chamber



- **NON-INTEGRATED** – this system operates through a hard-wired smartphone or tablet (Apple/Android)

Andrew Snell
+44 (0) 7967 300578
Andrew@pfc-eu.com

PLEASE CONSULT YOUR PRICE
GUIDE FOR ALL AVAILABLE OPTIONS
FOR THIS MODEL

Conventional





SALES & PRODUCT INFORMATION

Features

- Working range between 5 to 32% moisture
- Accuracy +/- 1%
- Provides live moisture data
- Provides average moisture of the previous bale
- Measurements taken 5 times per second
- Star Wheels fitted to underside of the bale chamber providing a long service life and easy fitment.
- Moisture is measured through the profile of the slice to achieve high levels of accuracy.

Benefits – Moisture Sensor

- **NO Calibration of moisture sensor when changing crops and bale density**
- Extended working day = More bales
- Non-stop baling = More bales
- Moisture accuracy = High quality bales

Available Options

- Wet bale paint marker system

Andrew Snell
+44 (0) 7967 300578
Andrew@pfc-eu.com

PLEASE CONSULT YOUR PRICE
GUIDE FOR ALL AVAILABLE OPTIONS
FOR THIS MODEL

Conventional

